

(19) World Intellectual Property  
Organization  
International Bureau



533278

(43) International Publication Date  
24 March 2005 (24.03.2005)


PCT

(10) International Publication Number  
**WO 2005/026705 A1**

- (51) International Patent Classification<sup>7</sup>: **G01N 21/35**, 21/39
- (21) International Application Number: PCT/EP2004/008584
- (22) International Filing Date: 30 July 2004 (30.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/502,282 12 September 2003 (12.09.2003) US
- (71) Applicant (for all designated States except US): **IR MICROSYSTEMS S.A.** [CH/CH]; PSE - Bât. C, CH-1015 Lausanne (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WILLING, Bert** [DE/CH]; Grand-Rue 10, CH-1162 St-Prex (CH). **KOHLI, Markus** [CH/CH]; Chemin du Banc-Vert 14, CH-1100 Morges (CH). **SEIFERT, Andreas** [DE/CH]; Chemin de l'Ochettaz 18, CH-1025 St-Sulpice (CH).
- (74) Agent: **ICB; Ingénieurs Conseils en Brevets SA**, Rue des Sors 7, CH-2074 Marin (CH).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: GAS DETECTION METHOD AND GAS DETECTOR DEVICE



(57) **Abstract:** The gas detector device comprises at least a VCSEL source (34, 36) and at least a light sensor (54, 56) for detecting a light beam (50, 52) having passed through a sample chamber (48) containing a given gas to be detected. The sensor is a photodiode in a first embodiment and its detection signal is time derivated by an electronic derivator (64) and then provided to two lock-in amplifiers (84, 86) in order to generate a F-detection and a 2F-detection, F being the frequency of a wavelength modulation of the source, and thus to provide two corresponding measuring signals the division of which gives a precise value of the gas concentration. In a second embodiment, the source is a pyroelectric sensor which directly provides a detection signal proportional to the time derivate of the light beam incident on this sensor. In this last case, the electronic derivator is thus eliminated.

WO 2005/026705 A1